

# Xtreme VAC

by 



## DCL800TM

- Kubota 4-cylinder  
gasoline engine rated 87HP
- 28" suction impeller
  - Hydraulic hose boom
  - Tandem rubber Torflex axles
  - 16" dia. x 120" rubber intake hose

The DCL800TM has the best suction of any unit in it's class. Contact your local Xtreme Vac dealer to order yours today!

\*Standard color is white.

\*Units may be shown with options.



Sold and Serviced by:



Sourcewell  
Awarded Contract  
Contract # 041217-ODB



# Specifications

# Self-Contained Debris Collector-Trailer Mounted

## Engine - Gas

Kubota WSG3800 3.8L 4-cylinder gasoline engine, rated at 87HP, meets EPA T2 & CARB T3 standards.

## Engine Controls

Electronic engine controls with safety shut down.

## Drive

Belt driven via a 4-groove power band.

## Hoist

Gear driven hydraulic pump powers 15.2 ton capacity underbody hoist that dumps to 52 degrees.

## Hopper

Container constructed of 11 gauge steel with vented top and side hinge rear doors. Available in 14, 20, 25 & 30 cu.yd. capacities.

## Axles

14CY - Dual 3.5" Torflex axles rated at 16,000 lbs.  
20CY - Dual 5" Torflex axles rated at 20,000 lbs.  
25/30CY-Dual 5" Torflex axles rated at 24,000 lbs.  
Equipped w/ electric brakes with break-away actuator.

## Tires

14CY - (4) ST235-85R16 radial tires on steel wheels.  
20/25/30CY - (8) 235/80R16E tires on steel wheels.

## Options

- 3-axis hose boom (up/dn, left/rt, in/out)
- Hydraulic parking jack in lieu of manual
- Fluid drive coupler in lieu of standard clutch
- Remote electric throttle for engine
- Urethane suction hose in lieu of rubber
- Urethane coated liners for blower housing
- Driver's side (street) pick up
- Perforated top screens with 3/16" holes
- Air Scoop or Bottom Exhaust on box
- Rotary self-cleaning radiator screen

## Engine - Option

John Deere 4045TFC03 4-cylinder diesel engine rated at 74HP - Final T4

## Radiator Screen

Boxed corrugated radiator screen constructed from perforated steel to increase air flow for better cooling.

## PTO

13" clutch assembly with 2.25" PTO shaft and safety engagement system.

## Hose Boom

Hydraulic hose boom powered by 12v electric / hydraulic pump.

## Hose

16" x 120" rubber suction hose with steel nozzle.

## Impeller

28" dia. suction impeller with six 3/8" thick T-1 abrasive resistant steel blades. Replaceable 1/4" thick steel liners.

## Fuel Tank

40-gallon polyethylene fuel tank.

## Pintle Eye

Heavy-duty height adjustable pintle eye with three quick release pins.

## Parking Jack

Manual parking jack with drop foot.

## Lights

LED type DOT trailer lights. Two amber LED flashers in the rear.

## Paint

All components are pre-painted with PPG paint - Hopper - standard white, other custom paint colors available as options.



\*Units may be shown with options.

